STT4501E2-D









Battery capacity 281.9 kWh Drive mode 4 x 2 Wheel base 3400 mm Capacity 75 t Range up to <u>120 km</u>

EQUIPMENT STT4501E2-D

FULL ELECTRIC TERMINAL TRACTOR

- + High efficiency, low consumption
- + Cost savings due to efficient system
- + Fast charging with dual guns
- Wide field experience in electric machine

Travel speed max. 40 km/h Empty weight 10000 kg Overall weight 85 000 kg Dimensions 5 850 x 2 500 x 3 500 mm Inner turning radius 6.6 meters

BATTERY

| Туре | Lithium iron phosphate (LFP) |
|-------------------------|--|
| Capacity | 281.9 kWh |
| Warranty period | The attenuation in 5 years shall not exceed 30 % |
| Fully discharge cycles | 3000 times |
| Cooling mode | liquid |
| Continuous working time | up to 120 km / up to 18 hours |

70 minutes

2*150 kW

CHARGER

Charging duration Charging power

ELECTRIC MOTORS

Power Torque 120 kW / 240 kW (single motor) 1 200 Nm / 2800 Nm

CHASSIS

| ve mode | 4 x 2 |
|---|---|
| b type | Cab forward |
| neel base | 3400 mm |
| le load F/R | 9.5t/30t |
| ar axle | Air suspended |
| ound clearance | 200 mm |
| ix. tract weight | 75t |
| adeability | 5% full load |
| n wheel – hydraulic adjustable | 1 180 mm – 1 530 mm |
| pacity 5th wheel | 32 t |
| celeration (0 to 30 km/h) | ≤ 25 seconds |
| e size | 12.00 R22.5-18PR |
| adeability n wheel – hydraulic adjustable pacity 5th wheel celeration (0 to 30 km/h) | 5% full load 1 180 mm – 1 530 mm 32 t ≤ 25 seconds |

TOP HIGHLIGHTS

LARGE LOAD CAPACITY, LONG BATTERY ENDURANCE

SANY electric terminal tractor use SANY's engineering vehicle heavy-load chassis. It has a maximum traction weight of 75 t; on the port ground, the battery endurance range can reach up to 120 km or the endurance time is up to 18 hours.

SAFE, EFFICIENT, LOW-COST

The protection level of the three-electric system meets IP67 or above and adopts CATL's advanced leakage detection system and SANY's remote monitoring system.

ECONOMICAL, EFFICIENT, RELIABLE

The tractor is equipped with an integrated thermal management system to ensure that the battery is always at a suitable temperature and has the lowest energy consumption. It has an auxiliary braking system to improve braking energy feedback and can operate continuously for more than 5 years.



Not all products are available in all markets. As part of our continuous improvement process, we reserve the right to modify specifications and designs without giving prior notice. The figures may contain additional options.



SANY EUROPE GmbH Sany Allee 1 D-50181 Bedburg Tel. +49 2272 90531 100 Fax +49 2272 90531 109 info@sanyeurope.com www.sanyeurope.com